FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Material Safety Data Sheet (MSDS)

Section 1 — Chemical Product and Company Identification

Aluminum Sulfate

Flinn Scientific, Inc. P.O. Box 219 Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Section 2 — Composition, Information on Ingredients

Aluminum Sulfate Synonyms: lake alum, aluminum trisulfate

CAS#: 17927-65-0

Section 3 — Hazards Identification

White/tan, odorless powder. Hydrolyzes to form Sulfuric Acid, which irritates tissues. Avoid all body tissue contact.

Section 4 — First Aid Measures

Call a physician, seek medical attention for further treatment, observation and support after first aid.

Inhalation: Remove to fresh air at once. If breathing has stopped give artificial respiration immediately.

Eye: Immediately flush with fresh water for 15 minutes.

External: Wash continuously with fresh water for 15 minutes.

Internal: Give large quantities of water. Call a physician or poison control at once.

Section 5 — Fire Fighting Measures

Non flammable solid. When heated to decomposition, emits toxic fumes of SOx. Fire Fighting Instructions: Use triclass, dry chemical fire extinguisher. Firefighters should wear PPE and SCBA with full facepiece operated in positive pressure mode.

Section 6 — Accidental Release Measures


Restrict unprotected personnel from area. Sweep up, place in sealed bag or container and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

Section 7 — Handling and Storage

Flinn Suggested Chemical Storage Pattern: Inorganic #2. Store with acetates, halides, sulfates, sulfites, thiosulfates and phosphates. Store in a cool dry place.

Section 8 — Exposure Controls, Personal Protection

Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, chemical-resistant gloves and chemical-resistant apron. Use exhaust ventilation to keep airborne concentrations low.



FLINN AT-A-GLANCE Health-0 Flammability-0 Reactivity-0 Exposure-1 Storage-0

0 is low hazard, 3 is high hazard

None Established

NFPA CODE

FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Material Safety Data Sheet (MSDS)

Section 9 — Physical and Chemical Properties

White/tan powder. Solubility: Soluble in water (36.4% at 20 C). Formula: Al2(SO4)3 14H2O-18H2O Formula Weight: 594.14

Section 10 — Stability and Reactivity

Avoid contact with strong oxidizers. When heated to decomposition, emits toxic fumes of SOx. Shelf life: indefinite

Section 11 — Toxicological Information

Acute effects: N.A. Chronic effects: N.A. Target organs: N.A. ORL-RAT LD50: 6207 mg/kg IHL-RAT LC50: N.A. SKN-RBT LD50: N.A.

N.A. = Not available, not all health aspects of this substance have been fully investigated.

Section 12 — Ecological Information

Data not yet available.

Section 13 — Disposal Considerations

Please consult with state and local regulations. Flinn Suggested Disposal Method #26a is one option.

Section 14 — Transport Information

Shipping Name: Not regulated Hazard Class: N/A UN Number: N/A

N/A = Not applicable

Section 15 — Regulatory Information

TSCA-listed, EINECS-listed (233-135-0).

Section 16 — Other Information

Consult your copy of the Flinn Scientific Catalog/Reference Manual for additional information about laboratory chemicals. This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. Flinn Scientific Inc. assumes no legal responsibility for use or reliance upon this data.

FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Flinn--"Your Safer Source for Chemicals"

flinn@flinnsci.com www.flinnsci.com P.O. Box 219 Batavia IL 60510 (800) 452-1261 Fax (866) 452-1436

Specific Gravity: 1.69

Melting point: 770 C

Aluminum Sulfate

Revision Date: February 26, 2003

MSDS #: 44.00